





NOTES:

- 1. AAR APPROVAL # E-149523.
- 2. THIS ASSEMBLY IS AAR AND DOT APPROVED.
- 3. QUICK DISCONNECT MEETS A-A-59326D.
- 4. ADAPTER THREADS PER FIGURE E-18 IN THE AAR TANK CAR MANUAL.
- 5. SPRAY OR WIPE DOWN WITH USDA WHITE MINERAL OIL OR VEGETABLE OIL AS A RUST INHIBITOR

REV	BY	DATE	DESCRIPTION
Α	CHL	6/24/10	NEW PART ADDED TO SYSTEM
В	WEB	1/23/14	THREAD CALL OUT WAS 4-4 UNC - 2A
С	WEB	12/7/15	ADDED NOTES, UPDATED TITLEBLOCK
D	BP	9/8/22	ADDED NOTE TO DRAWING TO APPLY MINERAL OR VEGETABLE OIL

UNLESS OTHERWISE SI DIMENSIONAL TOLER		DRAWN BY:	CHL		
FRACTIONAL:	±1/16	CHECKED BY:	VD		
X.XX: X.XXX:	±.03 ±.015	PROTOTYPE DATE:	2/2/2010	PART	
ANGULAR:	±1°	APPROVED FOR PRODUCTION BY:	VD		
DEBURR ALL SHARP ALL MACHINED SURFA HAVE A 125 RMS F	ACES TO	PRODUCTION DATE:	6/24/2010	MAT PRO	
UNLESS NOTED OTHE THIRD ANGLE PROJE	RWISE.	SIZE:	D	PART	T #:
		DRAWING #:	28092		

SALCO PRODUCTS, INC.

QUICK CONNECT ADAPTER 4" FLANGED

SEE BOM

"WAG0768

SHEET #: 1 OF 1 SCALE: 1:1

TE4IUTF7